

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: ETERNACRYL SATIN
Company name: Mandev
Studio 6 Bamwell Terrace
Alexandra Road
Grantham
Lincolnshire
NG31 7AL
United Kingdom
Tel: +44 (0) 1476 570 520
www.mandev.co.uk

In the event of an emergency contact Les Burrow at the above number.

2. COMPOSITION / INFORMATION ON INGREDIENTS

3. HAZARDS IDENTIFICATION

Main hazards: No significant hazard.

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: No symptoms.
Eye contact: There may be irritation and redness.
Inhalation: No symptoms.

4. FIRST AID MEASURES (ACTION)

Skin contact: Wash immediately with plenty of soap and water.
Eye contact: Bathe the eye with running water for 15 minutes.
Ingestion: Do not induce vomiting. Wash out mouth with water.

5. FIRE-FIGHTING MEASURES

6. ACCIDENTAL RELEASE MEASURES

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.
Clean-up procedures: Contain spillage with sand or earth, sweep up and dispose of in accordance with a recognised method of waste disposal.

7. HANDLING AND STORAGE

Storage conditions: Keep container tightly closed. Do not store below 10 degrees C and avoid freezing.
Suitable packaging: Must only be kept in original packaging to avoid contamination

SAFETY DATA SHEET
ETERNACRYL SATIN**8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

As with all chemicals, always wear protective garments and safety goggles. Apply in well ventilated area.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Liquid

Colour: White

Odour: Characteristic odour

Solubility in water: Water based

Viscosity: Non-viscous

Viscosity value: 25 sec

Viscosity test method: Flow time in seconds in a 3 mm ISO cup (ISO 2431)

Flash point°C: N/A

Relative density: 1.02

pH: 8.5

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.

Materials to avoid: Oxidising agents.

11. TOXICOLOGICAL INFORMATION**12. ECOLOGICAL INFORMATION**

Mobility: Non-volatile.

Bioaccumulative potential: No bioaccumulation potential.

13. DISPOSAL CONSIDERATIONS

Disposal operations: Disposal in accordance with local authority regulations.

Disposal of packaging: Dispose of as normal industrial waste.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION**ADR / RID**

UN no: 1263

Packing group: III

Classification code: F1

Shipping name: Laminate

Hazard ID no: 30

IMDG / IMO

UN no: 1263

Packing group: III

EmS: 3-05

Marine pollutant: NO

SAFETY DATA SHEET
ETERNACRYL SATIN

IATA / ICAO

UN no: 1263
Packing instructions: 309(P&CA); 310(PAO)

Packing group: III

15. REGULATORY INFORMATION

Hazard symbols: No significant hazard.

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. OTHER INFORMATION

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.